

**Multi-function ATM that maximizes the operating efficiency
Ideal ATM platform for drive-up**

Features

- **Powerful financial-transaction support**
With Microsoft Windows XP platform and Intel Pentium Processor, we guarantee faster and larger transaction support. Standardized design supports multi vendor solution.
- **High scalability**
Monimax 7600D is the multi-function ATM to support various additional financial services. It has interface system that is easy for expansion. Built-in check scanner and bill acceptor are optional.
- **Reliability**
Monimax 7600D guarantees high reliability and safety by satisfying demanded standards for supporting financial transaction such as UL 291 Level 1 and VISA certified encrypting PIN pad (Triple-DES)
- **Side Access Design for Easy Operations**
Monimax 7600D offers both side and rear access to provide flexibility for Drive-up installation and added operational convenience.



*Create your true ATM values
Design your own ATM portfolio*



Monimax 7600D supports not only traditional ATM transactions but also value-added services. It makes users feel comfortable to transact with the ADA standard compliance, sunlight viewable LCD and user-oriented module arrangement. It has the 15" LCD for both customer and supervisor.

System Control

Intel® Pentium® -IV Processor
Microsoft® Windows XP® platform

Communication

TCP/IP
Optional
Dial-up, Wireless connection

Application Software

NDC+, DDC912

Customer Display

15" TFT LCD
Sunlight viewable

Input Type

4 x 2 Function keys
(Optional touch screen)
4 x 4 Numeric keys
VISA/PCI EPP (Encrypting PIN pad)
ADA compliant
Supervisor Operation
15" TFT LCD, Touch screen

Card Handling

Dip type card reader
Optional
EMV Level 1, 2 compliant

Cash Dispensing

2 cassettes
3000 notes each
(Up to 4 Cassettes)
Bundle retraction

Depository

Envelope depository
Check scanner
Bundle note acceptor

Printers

Graphical thermal receipt printer
Electronic journal
Optional
Graphical thermal journal printer

Security

UL291 Level 1 safe
Mechanical combination lock
Optional
Electronic safe lock
KABA Mas Cencon safe lock

Miscellaneous

Heater
Lead-through indicator
Illuminated signage

Power Supply

AC 110 ~ 230V, 50 ~ 60Hz

Operating Environment

Temperature
-31°F ~ 122°F (-35°C ~ 50°C)
Humidity
25% ~ 86%

Dimension and Weight

Height : 61.2" (1,548mm)
Width : 32.6" (830mm)
Depth : 38.6" (982mm)
Weight : 1440 lbs (650kg)

Side access
Rear access

※ New technologies and components may be implemented in the products without prior notice, so Nautilus Hyosung reserves the right to change specifications accordingly.

